


# SFC/SFCS 止付螺絲固定式・撓性聯軸器 / Clamping Fix, Flexible Coupling



SFC/SFCS-  -  -   
 外徑                      D1                      D2  
 Diameter

◆尺寸表 / Dimension

單位/unit:mm

規格 No.	A	I	L	G	M	D1×D2/公差Tolerance(H8)		重量 Weight (g)
						min	max	
SFC-16	16	6.5	23	3	M3	4	8	9.5
SFC-20	20	7.5	26	3	M4	5	10	16
SFC-25	25	8.5	31	4	M4	5	12	30
SFC-32	32	12	41	6	M5	6	14	65
SFC-40	40	15	56	8.5	M5	8	20	120
SFC-50	50	18	71	10.5	M6	12	25	230
SFC-63	63	22	90	13	M8	15	35	470
SFCS-16	16	6.5	23	3	M3	4	8	28
SFCS-20	20	7.5	26	3	M4	5	10	45
SFCS-25	25	8.5	31	4	M4	6	12	95
SFCS-32	32	12	41	6	M5	6	14	220
SFCS-40	40	15	56	8.5	M5	8	20	350
SFCS-50	50	18	71	10.5	M6	12	25	700
SFCS-63	63	22	90	13	M8	15	35	1300

◆特性表 / Specification

規格 No.	常用扭力 Rated Torque (N.m)	最大扭力 Max. Torque (N.m)	最高轉數 Max. Rotational (rpm)	慣性矩 Moment of Inertia (Kg.m <sup>2</sup> )	剛性 靜扭力值 Staic Torional (N.m/rad)	容許偏心 Allowable Eccentricity Error (mm)	容許角度偏差 Allowable Angular Error (°)	容許軸向位移 Allowable End-Play (mm)
SFC-16	0.3	0.6	24000	3.3×10 <sup>-7</sup>	47	0.10	2	±0.4
SFC-20	0.5	1	19000	9.0×10 <sup>-7</sup>	120	0.10	2	±0.4
SFC-25	1	2	15000	2.6×10 <sup>-6</sup>	170	0.15	2	±0.5
SFC-32	2	4	12000	9.6×10 <sup>-6</sup>	280	0.15	2	±0.5
SFC-40	5	10	9600	3.2×10 <sup>-5</sup>	350	0.20	2	±0.5
SFC-50	10	20	7700	1.0×10 <sup>-4</sup>	590	0.20	2	±0.5
SFC-63	20	40	6100	3.2×10 <sup>-4</sup>	850	0.20	2	±0.5
SFCS-16	0.5	1	24000	8.4×10 <sup>-7</sup>	85	0.10	2	±0.3
SFCS-20	1	2	19000	2.4×10 <sup>-6</sup>	250	0.10	2	±0.3
SFCS-25	2	4	15000	6.8×10 <sup>-6</sup>	330	0.15	2	±0.4
SFCS-32	3.5	7	12000	2.6×10 <sup>-5</sup>	850	0.15	2	±0.5
SFCS-40	8	16	9600	8.7×10 <sup>-5</sup>	1000	0.20	2	±0.5
SFCS-50	15	30	7700	2.7×10 <sup>-4</sup>	1400	0.20	2	±0.5
SFCS-63	35	70	6100	8.4×10 <sup>-4</sup>	1800	0.20	2	±0.5