


SOL 止付螺絲十字滑動型 / Set Screw Oldham Coupling



SOL- - -
 外徑 D1 D2
 Diameter

◆尺寸表 / Dimension

單位 / unit:mm

規格 No.	A	I	L	G	M	D1 - D2		重量 Weight (g)
						min	max	
SOL-16	16	7	18	3.5	M3	4	6.35	7
SOL-20	20	9	23	4.5	M4	5	8	14
SOL-25	25	11	28	5.5	M5	5	10	27
SOL-32	32	13	33	6.5	M5	8	14	50
SOL-40	40	14	35	7	M6	10	16	80
SOL-50	50	17	38	8.5	M8	14	20	150
SOL-63	63	21	47	10.5	M10	15	25	300

◆特性表 / Specification

規格 No.	常用扭力 Rated Torque (N.m)	最大扭力 Max. Torque (N.m)	最高轉數 Max. Rotational (rpm)	慣性矩 Moment of Inertia (Kg.m ²)	剛性靜扭力值 Static Torsional Stiffness (N.m/rad)	容許偏心 Allowable Eccentricity Error (mm)	容許角度偏差 Allowable Errors (0)
SOL-16	0.7	1.4	9500	3.2×10^{-7}	31	1.0	3
SOL-20	1.2	2.4	7600	1.0×10^{-6}	60	1.5	3
SOL-25	2	4	6100	3.0×10^{-6}	140	2.0	3
SOL-32	4.5	9	4800	9.5×10^{-6}	280	2.5	3
SOL-40	9	18	3800	2.3×10^{-5}	540	3.0	3
SOL-50	18	36	3100	6.7×10^{-5}	820	3.5	3
SOL-63	36	72	2400	2.2×10^{-4}	1900	4.0	3

◆特性 / Features

- 高剛性 / High Rigidity
- 絕緣性佳 / Electrical Insulation
- 組合容易 / Easy Assembly
- 耐油性 / Oil Resistance
- 容許偏心、偏角大 / High Allowable Error of Eccentricity and Angularity Misalignment
- 緩衝材：工程塑膠 / Buffer Material : POM
- 固定方式：止付螺絲 / Fix Type : Set Screw Type
- 使用溫度範圍-30°C~100°C / Working range, -30°C~100°C Temperature